## MATERIAL SAFETY DATA SHEET

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Stain Halt Blocking Sealer-Primer Latex White

Product Code Identification Number: 215A100

MSDS Number:

GENERAL USE: Protective Coating



MANUFACTURER'S NAME		DATE PREPARED: May 2, 2006			Page 1 of 4			
Ace Hardware Paint Division		SUPERSEDES: February 18, 2002				014		
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHON	E NUMBE	ER FOR IN	IFORMAT	TION		
21901 South Central Avenue		(800) 311-						
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENCY TELEPHONE NUMBER						
Matteson, IL 60443-2800	USA	Infotrac (800) 535-5053 Outside USA (352) 323-3500						
DISTRIBUTOR'S NAME								
Ace Hardware Corporation								
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION						
2200 Kensington Court		(800) 311-						
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENO						
Oak Brook, IL 60523-2100	USA	Infotrac (8	00) 535-5	053 Out	side USA	(352) 32	3-3500	
SECTION	V <i>2 - HAZARD</i>	ous ingi	REDIE	V <i>TS</i>				
		%	% OSHA PEI		ACGIH TWA		SARA	RQ
HAZARDOUS COMPONENTS	CAS#	(by weight)	PPM	MG/M3	PPM	MG/M3	TITLE III	LBS
		(by weight)	FFIVI	IVICI/IVIO	1 1 171			
Ethylene glycol (a,b,c)	107-21-1	1 - 5	FFIVI	IVIG/IVIS	39.4 C	127 C	Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFIVI	IVIG/IVIO			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFIVI	Wanvis			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFWI	IWG/WI3			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFIVI	MG/M3			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFWI	INIC/NIS			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFIVI	WG/WS			Yes	500
Ethylene glycol (a,b,c)	107-21-1	( ) 0 ,	FFIVI	, waws			Yes	50
Ethylene glycol (a,b,c)  (a,c) See Section 15	107-21-1	( ) 0 ,	FFIVI	WG/WS			Yes	50
(a,c) See Section 15 b) A "C" in the OSHA PEL or ACGIH TWA column indica		1 - 5			39.4 C	127 C		
		1 - 5			39.4 C	127 C		

## SECTION 3 - HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

WARNING! Harmful or fatal if swallowed, harmful if inhaled or absorbed through the skin. May cause allergic skin reaction. May cause irritation to skin, eyes, and respiratory tract. Affects central nervous system Hazard symbols for this product - Not classified. Risk Phrases -Not classified

#### POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations in the form of vapors or mists are irritating to the respiratory tract; may cause headache, dizziness, nausea

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: High vapor concentration or contact may cause irritation and discomfort.

INGESTION: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, or possible convulsions or coma; large doses may be fatal.

CARCINOGENICITY No No NTP? IARC MONOGRAPHS? OSHA REGULATED?

This product contains trace amounts of the following substances known to the state of California to cause cancer: 1,4 Dioxane, Ethylene Oxide, and Acetaldehyde.

#### MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Stain Halt Blocking Sealer-Primer Latex White

May 2, 2006

## SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; if symptoms persist seek medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.

## SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

FLAMMABLE LIMITS

LEL: Not applicable UEL: Not applicable

None

Non-flammable

**AUTOIGNITION TEMPERATURE:** Not determined NFPA CLASS:

GENERAL HAZARDS: Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

#### **EXTINGUISHING MEDIA**

Carbon dioxide, water, water fog, dry chemical, chemical foam

#### FIRE FIGHTING PROCEDURES

Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

None

#### HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes, oxides of carbon

## SECTION 6 - ENVIRONMENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for complete regulations concerning reporting requirements.

## SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **ENGINEERING CONTROLS**

The use of local exhaust ventilation is recommended. No other special controls are indicated.

#### PERSONAL PROTECTION:

RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations: if TWA exceeds limits. NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.

EYE PROTECTION: Protective eyeglasses or chemical safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

Page 2 of 4

#### MATERIAL SAFETY DATA SHEET PRODUCT NAME: Stain Halt Blocking Sealer-Primer Latex White Page 3 of 4 May 2, 2006 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES VAPOR PRESSURE (MM Hg) VAPOR DENSITY (AIR = 1) 17 mm Hg @ 20° C SPECIFIC GRAVITY (WATER = 1) **EVAPORATION RATE (WATER = 1)** SOLUBILITY IN WATER FREEZING POINT Dispersible 32° F (0° C) APPEARANCE AND ODOR pН White viscous liquid, slight ammonia odor 8.5 - 9.0**BOILING POINT** PHYSICAL STATE 180°F (82°C) Liquid VISCOSITY (KREBS) 80 - 85 SECTION 10 - STABILITY AND REACTIVITY STABILITY UNSTABLE: CONDITIONS TO AVOID: STABLE: XXX Extreme temperatures, keep from freezing INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. MAY OCCUR: HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID: WILL NOT OCCUR: XXX None SECTION 11 - TOXICOLOGICAL INFORMATION LD50 of Ingredient LC50 of Ingredient CAS# **EINECS#** Hazardous Ingredients (Specify Species and Route) (Specify Species) 4700 mg / kg 10876 mg / kg Ethylene glycol (a,b,c) 107-21-1 203-473-3 Oral - rat Inhalation - rat

## SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

## SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Product is classified as non hazardous, however, non-hazardous materials may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

## SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Not Regulated

DOT HAZARD CLASS / Pack Group: None / None

REFERENCE: Not Applicable

UN / NA IDENTIFICATION NUMBER: None

LABEL: None Required

HAZARD SYMBOLS: None

IATA HAZARD CLASS / Pack Group: None

IMDG HAZARD CLASS: None RID/ADR Dangerous Goods Code: None UN TDG Class / Pack Group: None

Hazard Identification Number (HIN): None

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

# MATERIAL SAFETY DATA SHEET PRODUCT NAME: Stain Halt Blocking Sealer-Primer Latex White May 2, 2006 Page 4 of 4

## SECTION 15 - REGULATORY INFORMATION

#### TSCA (Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

#### SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories

Immediate health

#### 313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of SARA Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

#### CERCLA (Comprehensive Response Compensation and Liability Act)

(c) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, according to 40 CFR 302.

#### California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

#### **CPR (Canadian Controlled Products Regulations)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: Not controlled

## IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

#### DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

#### EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

EC Risk Phrases Not classified	SYMBOL(S) REQUIRED FOR LABEL None	EC Safety Phrases S2 Keep out of the reach of children. S24/25 Avoid contact with skin and eyes									
SECTION 16 - OTHER INFORMATION											
No specific notes.											
HMIS HAZARD RATINGS	HEALTH	1	* = Chronic Health Hazard	2 = MODERATE							
	FLAMMABILITY	0	0 = INSIGNIFICANT 1 = SLIGHT	3 = HIGH							
	PHYSICAL HAZARD	0	i – Sligni	4 = EXTREME							
REVISION SUMMARY:	This MSDS has been revised in the following sections: Format revision										
MSDS Prepared by:	Comprehensive Data Base, In P.O. Box 5604 Lakeland, FL 33807 USA (863) 644 - 3298 www.com		ase.com								

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.