

MINWAX -- 2716 MINWAX WOOD FINISH DARK WALNUT  
MATERIAL SAFETY DATA SHEET  
NSN: 801000F035145  
Manufacturer's CAGE: 0K1A4  
Part No. Indicator: B  
Part Number/Trade Name: 2716 MINWAX WOOD FINISH DARK WALNUT

=====  
General Information  
=====

Company's Name: MINWAX CO  
Company's Street: 15 MERCEDES DRIVE  
Company's P. O. Box: 438  
Company's City: MONTVALE  
Company's State: NJ  
Company's Country: US  
Company's Zip Code: 07645-5000  
Company's Emerg Ph #: 201-391-0253/201-573-5700  
Company's Info Ph #: 201-573-5700/201-391-0253  
Record No. For Safety Entry: 001  
Tot Safety Entries This Stk#: 001  
Status: FE  
Date MSDS Prepared: 02MAR95  
Safety Data Review Date: 17JAN97  
Preparer's Company: MINWAX CO  
Preparer's St Or P. O. Box: 15 MERCEDES DRIVE  
Preparer's City: MONTVALE  
Preparer's State: NJ  
Preparer's Zip Code: 07645-5000  
MSDS Serial Number: CDCQK

=====  
Ingredients/Identity Information  
=====

=====  
Physical/Chemical Characteristics  
=====

Appearance And Odor: CLEAR AMBER TO OPAQUE EARTH-TONE, SLIGHTLY VISCOUS  
LIQUID W/HYDROCARBON ODOR  
Specific Gravity: 0.805-0.878  
Solubility In Water: INSOLUBLE

=====  
Fire and Explosion Hazard Data  
=====

Flash Point: 106F  
Flash Point Method: TCC  
Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2  
Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. PRODUCT  
MAY BE REIGNITED ON SURFACE OF WATER. WEAR SCBA & PROTECTIVE CLOTHING. USE  
WATERSPRAY TO COOL FIRE-EXPOSED CONTAINER  
Unusual Fire And Expl Hazrds: CONTAINERS EXPOSED TO INTENSE HEAT FROM  
FIRES SHOULD BE COOLED W/WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH  
COULD RESULT IN CONTAINER RUPTURE.

=====  
Reactivity Data  
=====

Stability: YES  
Cond To Avoid (Stability): USING/STORING NEAR HEAT, SPARKS, FLAME/OTHER  
IGNITION SOURCES  
Materials To Avoid: STRONG OXIDIZING AGENTS  
Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO  
Hazardous Poly Occur: NO

=====  
Health Hazard Data  
=====

Route Of Entry - Inhalation: YES  
Route Of Entry - Skin: NO  
Route Of Entry - Ingestion: YES  
Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.  
Carcinogenicity - NTP: NO  
Carcinogenicity - IARC: YES

Carcinogenicity - OSHA: NO

Explanation Carcinogenicity: SEE INGREDIENTS.

Signs/Symptoms Of Overexp: IRRITATION

Emergency/First Aid Proc: INHALATION: IMMEDIATELY REMOVE TO FRESH AIR.  
SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: IMMEDIATELY FLUSH THOROUGHLY W/  
WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

=====  
Precautions for Safe Handling and Use  
=====

Steps If Matl Released/Spill: ABSORB W/SAND/OTHER SUITABLE ABSORBENT  
MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY.  
DIKE AROUND W/ABSORBENT. TRANSFER LIQUIDS & CONTAMINATED DIKING MATERIAL TO  
SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL  
REGULATIONS.

Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT/SPARKS/OTHER  
IGNITION SOURCES. CLOSE CONTAINER AFTER EACH USE. USE ONLY W/ADEQUATE  
VENTILATION. KEEP OUT CHILDREN'S REACH.

Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN & EYES.  
AVOID INHALATION. IF USING INDOORS, OPEN ALL WINDOWS & DOORS TO MAKE SURE  
THERE IS FRESH AIR MOVEMENT.

=====  
Control Measures  
=====

Respiratory Protection: REQUIRED

Ventilation: REQUIRED

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES  
=====

Transportation Data  
=====

Disposal Data  
=====

Label Data  
=====